



PCF40/50

Proudly made in the UK, Precision's high performance easy to use Blast Chiller / Freezer/ Thawing cabinets have been designed to provide energy efficient and reliable Chilling, Freezing & Thawing solutions in commercial kitchens all around the world.

Available in under counter and reach-in models with capacities ranging from 15kg to 50kg per 90 minutes chilling or 240 minute freezing cycle. All models accommodate gastronorm GN1/1 pans.

Key Features:

Stainless Steel Interior & Exterior

Intuitive Digital Control Panel

Blast Chill +90 To +3°C In 90 Minutes*

Chill Store 0 / +3°C

Blast Freeze +90 To -18°C in 240 Minutes*

Freeze Store -18 / -20°C

Choice Of Time Or Food Probe Control

Automatic Storage At End Of Each Blast Cycle

Automatic Defrost At End Of Each Blast Cycle

Thawing Mode For Controlled Defrosting Of Frozen Food

R452A Refrigerant

Zero ODP Injected Polyurethane Insulation

Ergonomic Flush Door Handle

Gastronorm Shelving System - Anti Tilt Slides

Condensing Unit Safety System To Protect Compressor From Blocked Condensers

Self Closing Door

Heavy Duty Brake & Swivel Castors

Automatic Condensate Vaporiser System

*All Quoted Times/Weights Depend On Product, Water Content & Density



PCF15

Options:

Nylon Coated Shelves - GN1/1


Stainless Steel Shelves - GN1/1

GN1/1 Pan Set - 40mm Deep

Stainless Steel Back

Adjustable Legs

Left Hand Hinged Door



Model	PCF15	PCF40	PCF50
Type	Blast Chiller / Freezer	Blast Chiller / Freezer	Blast Chiller / Freezer
Material	ST/ST Int/Ext	ST/ST Int/Ext	ST/ST Int/Ext
Shelf Size	GN1/1	GN1/1	GN1/1
Pairs of Tray Slides Supplied	5	10	15
Max Number of Trays/Shelves (not supplied)	5	10	15
Temperature Range	+90 / +3°C +90 / -18°C	+90 / +3°C +90 / -18°C	+90 / +3°C +90 / -18°C
Exterior WxDxH (mm)	720x820x870	720x820x1765	720x820x1765
Chilling / Freezing Capacity (kg)	15	40	50
Weight (KG)	85	180	185
Refrigerant / GWP	R452A / 2141	R452A / 2141	R452A / 2141
Refrigeration Watts (+45°C Condensing)	1686 / 560	2152 / 628	2620 / 829
Evaporating Temp	-5°C / -30°C	-5°C / -30°C	-5°C / -30°C
Heat Rejection Watts*	2872	3855	5159
Noise Output (dBa)	85	92	96
Power	230 / 50 / 1 13 Amp Supply	230 / 50 / 1 13 Amp Supply	230 / 50 / 1 16 Amp Supply
Running Amps	5.7 / 4.4	10.2 / 6.6	13 / 11
Total Electrical Load - kW	1.61	1.86	2.53
Energy Consumption / 24hrs - kWh**	N/A	N/A	N/A
Energy Consumption / Year (AEC) - kWh**	N/A	N/A	N/A
Energy Efficiency Class**	N/A	N/A	N/A

* Heat Rejection is taken at the listed evaporating and condensing condition. Watts is calculated using total power of the cabinet.

** Tested to BS EN ISO 22041

We are constantly innovating and improving our products. Please scan QR code for the most up-to-date version of this spec sheet:

